


Si PIN photodiode



S12158-01CT

COB type, applicable to lead-free solder reflow

The S12158-01CT is a Si PIN photodiode for visible to near infrared range and is compatible with lead-free solder reflow processes. The small and thin leadless package allows reducing the mount area on a printed circuit board.

Features

- COB type, small and thin leadless package
- Applicable to lead-free solder reflow
- Photosensitive area: 2.77 × 2.77 mm
- High sensitivity: 0.7 A/W ($\lambda=960$ nm)

Applications

- FSO (free space optics)
- Optical switches
- Laser radar, etc.

Structure

Parameter	Specification	Unit
Photosensitive area	2.77 × 2.77	mm
Package	Glass epoxy	-
Seal material	Epoxy resin	-

Absolute maximum ratings

Parameter	Symbol	Condition	Value	Unit
Reverse voltage	V_R max	$T_a=25$ °C	20	V
Operating temperature	T_{opr}		-25 to +85	°C
Storage temperature	T_{stg}		-40 to +100	°C
Reflow soldering conditions*1	T_{sol}		Peak temperature 260 °C, 2 times (see page 4)	-


Note: Exceeding the absolute maximum ratings even momentarily may cause a drop in product quality. Always be sure to use the product within the absolute maximum ratings.

*1: JEDEC level 4


Electrical and optical characteristics ($T_a=25$ °C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Spectral response range	λ		-	320 to 1100	-	nm
Peak sensitivity wavelength	λ_p		-	960	-	nm
Photosensitivity	S	$\lambda=\lambda_p$	0.6	0.7	-	A/W
Dark current	I_D	$V_R=12$ V	-	0.1	10	nA
Temperature coefficient of I_D	TC_{ID}	$V_R=12$ V	-	1.15	-	times/°C
Cutoff frequency	f_c	$V_R=12$ V, $R_L=50$ Ω -3 dB	10	25	-	MHz
Terminal capacitance	C_t	$V_R=12$ V, $f=1$ MHz	-	15	30	pF


Spectral response




Dark current vs. reverse voltage




Terminal capacitance vs. reverse voltage



Dark current vs. ambient temperature




Directivity



KPINB0383EA


Dimensional outline (unit: mm)



①② Anode (common)
 ③④ Cathode (common)
 Tolerance unless otherwise noted: $\pm 0.1, \pm 2^\circ$
 Chip position accuracy with respect to package dimensions marked*
 $X, Y \leq \pm 0.2, \theta \leq \pm 2^\circ$
 Standard packing state: reel (2000 pcs/reel)


KPINA0113EA

Product orientation on reel




KPIN0020EA

Recommended land pattern (unit: mm)



Recommended temperature profile of reflow soldering (typical example)



- After unpacking, store this device in an environment at a temperature of 5 to 30 °C and a humidity below 70%, and perform reflow soldering on this device within 72 hours.
- The effect that the product receives during reflow soldering varies depending on the circuit board and reflow oven that are used. Before actual cleaning, check for any problems by testing out the cleaning methods in advance. A sudden temperature rise and cooling may be the cause of trouble, so make sure that the temperature change is within 4 °C per second.

Information described in this material is current as of October, 2012.

Product specifications are subject to change without prior notice due to improvements or other reasons. Before assembly into final products, please contact us for the delivery specification sheet to check the latest information.

The product warranty is valid for one year after delivery and is limited to product repair or replacement for defects discovered and reported to us within that one year period. However, even if within the warranty period we accept absolutely no liability for any loss caused by natural disasters or improper product use.

Copying or reprinting the contents described in this material in whole or in part is prohibited without our prior permission.

HAMAMATSU

www.hamamatsu.com

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81) 53-434-3311, Fax: (81) 53-434-5184

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 8152-375-0, Fax: (49) 8152-265-8

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Thorshamnsgatan 35 16440 Kista, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1 int. 6, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741

China: Hamamatsu Photonics (China) Co., Ltd.: 1201 Tower B, Jiaming Center, No.27 Dongsanhuan Beilu, Chaoyang District, Beijing 100020, China, Telephone: (86) 10-6586-6006, Fax: (86) 10-6586-2866