

# Si PIN photodiode

S14605



## Large-area Si PIN photodiode for direct radiation detection

The S14605 is an unsealed type large-area Si PIN photodiode for direct radiation detection. It can detect high-energy radiation with high efficiency.

### Features

- High quantum efficiency
- High energy resolution
- Low capacitance

### Applications

- Direct X-ray detection
- Radiation detection  
( $\alpha$  rays,  $\beta$  rays, charged particles, etc.)

### Structure

Parameter	Specification	Unit
Photosensitive area	9 × 9	mm
Depletion layer	0.5	mm
Package	Ceramic	-
Window material	None	-

### Absolute maximum ratings

Parameter	Symbol	Condition	Value	Unit
Reverse voltage	V <sub>R</sub>		150	V
Operating temperature	T <sub>opr</sub>	No dew condensation*1	-20 to +60	°C
Storage temperature	T <sub>stg</sub>	No dew condensation*1	-20 to +80	°C


\*1: When there is a temperature difference between a product and the surrounding area in high humidity environment, dew condensation may occur on the product surface. Dew condensation on the product may cause deterioration in characteristics and reliability.

Note: Exceeding the absolute maximum ratings even momentarily may cause a drop in product quality. Always be sure to use the product within the absolute maximum ratings.


### Electrical and optical characteristics (T<sub>a</sub>=25 °C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
X-ray energy	-		-	-	50	keV
Dark current	I <sub>D</sub>	V <sub>R</sub> =100 V	-	8	30	nA
Dark current temperature coefficient	I <sub>CD</sub>	V <sub>R</sub> =100 V	-	1.12	-	times/°C
Cutoff frequency	f <sub>c</sub>	V <sub>R</sub> =100 V, R <sub>L</sub> =50 Ω λ=780 nm, -3 dB	-	20	-	MHz
Terminal capacitance	C <sub>t</sub>	V <sub>R</sub> =100 V, f=10 kHz	-	25	40	pF


## Photosensitivity vs. X-ray energy (theoretical value)




## Dark current vs. reverse voltage



## Terminal capacitance vs. reverse voltage



### Dimensional outline (unit: mm)



### Related information

[www.hamamatsu.com/sp/ssd/doc\\_en.html](http://www.hamamatsu.com/sp/ssd/doc_en.html)

#### Precautions

- Disclaimer
- Metal, ceramic, plastic package products
- Unsealed products

#### Technical information

- Si photodiode / Application circuit examples

Information described in this material is current as of January 2020.

Product specifications are subject to change without prior notice due to improvements or other reasons. This document has been carefully prepared and the information contained is believed to be accurate. In rare cases, however, there may be inaccuracies such as text errors. Before using these products, always contact us for the delivery specification sheet to check the latest specifications.

The product warranty is valid for one year after delivery and is limited to product repair or replacement for defects discovered and reported to us within that one year period. However, even if within the warranty period we accept absolutely no liability for any loss caused by natural disasters or improper product use. Copying or reprinting the contents described in this material in whole or in part is prohibited without our prior permission.

# HAMAMATSU

[www.hamamatsu.com](http://www.hamamatsu.com)

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81)53-434-3311, Fax: (81)53-434-5184

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, Bridgewater, N.J. 08807, U.S.A., Telephone: (1)908-231-0960, Fax: (1)908-231-1218, E-mail: [usa@hamamatsu.com](mailto:usa@hamamatsu.com)

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-265-8, E-mail: [info@hamamatsu.de](mailto:info@hamamatsu.de)

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10, E-mail: [infos@hamamatsu.fr](mailto:infos@hamamatsu.fr)

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44)1707-294888, Fax: (44)1707-325777, E-mail: [info@hamamatsu.co.uk](mailto:info@hamamatsu.co.uk)

North Europe: Hamamatsu Photonics Norden AB: Torshamnsgatan 35 16440 Kista, Sweden, Telephone: (46)8-509 031 00, Fax: (46)8-509 031 01, E-mail: [info@hamamatsu.se](mailto:info@hamamatsu.se)

Italy: Hamamatsu Photonics Italia S.r.l.: Strada della Moia, 1 int. 6, 20020 Arese (Milano), Italy, Telephone: (39)02-93 58 17 33, Fax: (39)02-93 58 17 41, E-mail: [info@hamamatsu.it](mailto:info@hamamatsu.it)

China: Hamamatsu Photonics (China) Co., Ltd.: B1201, Jianning Center, No.27 Dongsanhuan Beilu, Chaoyang District, 100020 Beijing, P.R.China, Telephone: (86)10-6586-6006, Fax: (86)10-6586-2866, E-mail: [hpc@hamamatsu.com.cn](mailto:hpc@hamamatsu.com.cn)

Taiwan: Hamamatsu Photonics Taiwan Co., Ltd.: 8F-3, No. 158, Section2, Gongdao 5th Road, East District, Hsinchu, 300, Taiwan R.O.C. Telephone: (886)3-659-0080, Fax: (886)3-659-0081, E-mail: [info@hamamatsu.com.tw](mailto:info@hamamatsu.com.tw)