

S12053-02/-05/-10
S9075, S5344, S5345

Short wavelength type APD, for 600 nm band

These are short wavelength APDs with improved sensitivity in the UV to visible range. They offer high gain, high sensitivity, and low noise in the short wavelength range. They are suitable for applications such as low-light-level measurement and analytical instrument.

Features

➔ High sensitivity and low noise in UV to visible range

Applications

➔ Low-light-level measurement

➔ Analytical instrument

Structure / Absolute maximum ratings

Type no.	Dimensional outline/ Window material*1	Package	Effective photosensitive*2 area size (mm)	Absolute maximum ratings	
				Operating temperature Topr (°C)	Storage temperature Tstg (°C)
S12053-02	(1)/U	TO-18	φ0.2	-20 to +60	-55 to +100
S12053-05			φ0.5		
S12053-10			φ1.0		
S9075	(2)/U	TO-5	φ1.5		
S5344			φ3.0		
S5345			(3)/U		

Note: Exceeding the absolute maximum ratings even momentarily may cause a drop in product quality. Always be sure to use the product within the absolute maximum ratings.

*1: U=UV glass


*2: Area in which a typical gain can be obtained

Electrical and optical characteristics (Typ. Ta=25 °C, unless otherwise noted)

Type no.	Spectral response range λ (nm)	Peak*3 sensitivity wavelength λp (nm)	Photo-sensitivity S M=1 λ=620 nm (A/W)	Quantum efficiency QE M=1 λ=620 nm (%)	Breakdown voltage VBR ID=100 μA		Temp. coefficient of VBR (V/°C)	Dark*3 current ID		Cutoff*3 frequency fc RL=50 Ω (MHz)	Terminal*3 capacitance Ct (pF)	Excess*3 noise figure x λ=650 nm	Gain M λ=650 nm
					Typ. (V)	Max. (V)		Typ. (nA)	Max. (nA)				
S12053-02	200 to 1000	620	0.42	80	150	200	0.14	0.2	5	900	2	0.28	50
S12053-05										400	5		
S12053-10										250	15		
S9075										100	30		
S5344										25	120		
S5345										8	320		


*3: Values measured at a gain listed in the characteristics table

Spectral response




KAPDB0010ED

Quantum efficiency vs. wavelength




KAPDB0023EB

Dark current vs. reverse voltage




KAPDB0009EE

Gain vs. reverse voltage




KAPDB0011EC

Terminal capacitance vs. reverse voltage





Excess noise factor vs. gain




Dimensional outlines (unit: mm)

(1) S12053-02/-05/-10





Distance from photosensitive area center to cap center
 $-0.2 \leq X \leq +0.2$
 $-0.2 \leq Y \leq +0.2$




The glass window may extend a maximum of 0.1 mm above the upper surface of the cap.

KAPDA0014EB

(2) S9075, S5344





Distance from photosensitive area center to cap center
 $-0.3 \leq X \leq +0.3$
 $-0.3 \leq Y \leq +0.3$




The glass window may extend a maximum of 0.2 mm above the upper surface of the cap.

KAPDA0015EB

(3) S5345



Distance from photosensitive area center to cap center
 $-0.4 \leq X \leq +0.4$
 $-0.4 \leq Y \leq +0.4$



The glass window may extend a maximum of 0.2 mm above the upper surface of the cap.

KAPDA0016EC

Precautions

Long-term exposure to UV will cause product characteristics deteriorate.
 Avoid exposing the products to any unnecessary UV irradiation.

Related information

http://www.hamamatsu.com/sp/ssd/doc_en.html

Precautions

- Notice
- Metal, ceramic, plastic package products / Precautions

Technical information

- Si APD / Technical information

Information described in this material is current as of October, 2013.

Product specifications are subject to change without prior notice due to improvements or other reasons. This document has been carefully prepared and the information contained is believed to be accurate. In rare cases, however, there may be inaccuracies such as text errors. Before using these products, always contact us for the delivery specification sheet to check the latest specifications.

The product warranty is valid for one year after delivery and is limited to product repair or replacement for defects discovered and reported to us within that one year period. However, even if within the warranty period we accept absolutely no liability for any loss caused by natural disasters or improper product use.

Copying or reprinting the contents described in this material in whole or in part is prohibited without our prior permission.

HAMAMATSU

www.hamamatsu.com

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81) 53-434-3311, Fax: (81) 53-434-5184

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 8152-375-0, Fax: (49) 8152-265-8

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Thorshamnsgatan 35 16440 Kista, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1 int. 6, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741

China: Hamamatsu Photonics (China) Co., Ltd.: 1201 Tower B, Jiaming Center, No.27 Dongsanhuan Beilu, Chaoyang District, Beijing 100020, China, Telephone: (86) 10-6586-6006, Fax: (86) 10-6586-2866